

JUN 21 2007

IN THE SPECIFICATION

Please amend the abstract as indicated in the following paragraph:

An apparatus instrument assembly and method are provided described for precisely isolating a target lesion in a patient's body tissue, resulting in a high likelihood of "clean" margins about the lesion when it is removed for diagnosis and/or therapy. This approach advantageously will often result in the ability to both diagnose and treat a malignant lesion with only a single percutaneous procedure, with no follow-up percutaneous or surgical procedure required~~[[.]]~~ while ~~minimizing the risk of migration of possibly cancerous cells from the lesion to surrounding tissue or the bloodstream.~~ In particular, the apparatus ~~comprises a biopsy instrument~~ assembly having has a distal end adapted for entry into the patient's body, a longitudinal shaft, and a cutting element disposed along a distal portion of the shaft. The cutting element is actuatable between a radially retracted position within an electrically insulating recess and a radially extended position~~[[.]]~~ Advantageously, ~~the instrument and~~ is rotatable about its axis in the radially extended position to isolate a desire tissue specimen from surrounding tissue by defining a peripheral margin about the tissue specimen. ~~Once the tissue specimen is isolated, it may be segmented by further manipulation of the cutting element, after which the tissue segments are preferably individually removed from the patient's body through a cannula or the like. Alternatively, the specimen may be encapsulated and removed as an intact piece.~~